

CF3-A Calcite Filter

Light Commercial Automatic

WATERWAYS

Quality ways with water

Est. 1987

Product Description: Calcite is a food grade safe to drink pH adjustment mineral readily absorbed via flow of water through the material. Calcite filters are used to raise pH in acidic waters to a neutral level, typically pH 7.0 is optimum. Low pH waters are very corrosive and outside of safe water guidelines.

Specifications

Type	Automatic Calcite pH Correction Filter	
Description	Self standing pressure vessel (blue) with top mounted valve	
Media Tank	16" (41cm) x 65" (165cm) wound fibreglass pressure vessel	
Media	125kg of calcite	
Control Valve	Fleck 5000 electronic valve, fast and rapid rinse, full adjustable function, 1-99 day backwash	
Flow Rate	Continuous	50 litres per minute
	Peak	60 litres per minute
Pressure	Maximum	600 kpa (85 psi)
	Minimum	175 kpa (25 psi)
Pipe Sizes	Inlet/outlet	3/4" (20mm)
	Drain	1/2" (12mm)
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.

To us it's more than just water...

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160

PO Box 443 Lonsdale DC SA 5160

Telephone 08 8186 0189 Facsimile 08 8382 7488

Email: enquiries@waterwaysproducts.com

www.waterwaysproducts.com