

SA2 Mixed Bed Filter

Light Commercial Automatic

WATERWAYS
Quality ways with water

Est.1987

Product Description: Mixed bed filters are used for sediment removal over a wide range of flow rates. Due to a much larger surface area and the ability to be backwashed the dirt holding/handling capability of a mixed bed filter is far superior to cartridges. The beds can be made up of different filtering sands and filtration media.

Specifications

| | | |
|---------------|--|----------------------|
| Type | Automatic Mixed Bed Filter | |
| Description | Self standing pressure vessel (blue) with top mounted valve | |
| Media Tank | 13" (33cm) x 54" (137cm) wound fibreglass pressure vessel | |
| Media | 53kg of mixed media Sand, anthracite and gravels | |
| Control Valve | Fleck 5000 electronic valve, fast and rapid rinse, full adjustable function, 1-99 day backwash | |
| Flow Rate | Continuous | 35 litres per minute |
| | Peak | 40 litres per minute |
| Pressure | Maximum | 600 kpa (85psi) |
| | Minimum | 175 kpa (25psi) |
| Pipe Sizes | Inlet/outlet | 3/4" (20mm) |
| | Drain | 1/2" (12mm) |
| Voltage | 240 volts with 24 volts step down transformer | |

Note: Product specifications are a guide only and can change without notice.

To us it's more than just water...