

1354-9100 Twin Tank Softener

Commercial Automatic

WATERWAYS

Quality ways with water

Est-1987

Product Description: Water softeners are typically used for removing calcium carbonate, manganese, iron and hardness from water sources and are regenerated by brine solutions. The treated water is soft and non scaling/staining. Commercial systems are available in single or twin (duplex) models and domestic units are available in cabinet style models.

Specifications

Type	Automatic Water Softener	
Description	Self standing pressure vessel (blue) with top mounted valve and separate brine tank (black)	
Capacity	38,000 litres at 100 mg/l hardness	
Media tank	13" (33cm) x 54" (137cm) wound fibreglass pressure vessel	
Resin Capacity	112 litres of fine mesh cation resin	
Control Valve	Fleck 9100 electronic 5 stage regeneration fully adjustable functions Microprocessor control	
Brine tank	18" (46cm) x 40" (102cm) with lid	
Flow Rate	Continuous	50 litres per minute
	Peak	60 litres per minute
Pressure	Maximum	600 kpa (85 psi)
	Minimum	175 kpa (25 psi)
Pipe Sizes	Inlet/outlet	1" (25mm)
	Drain	1/2" (12mm)
Salt Usage	12kg per regeneration	
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160

PO Box 443 Lonsdale DC SA 5160

Telephone 08 8186 0189 Facsimile 08 8382 7488

Email: enquiries@waterwaysproducts.com

www.waterwaysproducts.com