

## **1665**·**5000** Water Softener

**Commercial Automatic** 

## **WATERWAYS**

Quality ways with water

.x.7987

**Product Description**: Water softeners are typically used for removing calcium carbonate, manganese, iron and hardness from water sources and are regenerated by brine solutions. The treated water is soft and non scaling/staining. Commercial systems are available in single or twin (duplex) models and domestic units are available in cabinet style models.

## **Specifications**

•		
Туре	Automatic Water Softener	
Description	Self standing pressure vessel (blue) with top mounted valve and separate brine tank (black)	
Capacity	60,000 litres at 100 mg/l hardness	
Media Tank	16" (41cm) x 65" (165cm) wound fibreglass pressure vessel	
Resin Capacity	100 litres of fine mesh cation resin	
Control Valve	Fleck 5000 electronic 5 stage regeneration fully adjustable functions Microprocessor control	
Brine Tank	18" (46cm) x 40" (102cm) with lid	
Flow Rate	Continuous Peak	50 litres per minute 60 litres per minute
Pressure	Maximum Minimum	600 kpa (85psi) 175 kpa (25psi)
Pipe Sizes	Inlet/outlet Drain	3/4" (20mm) 1/2" (15mm)
Salt Usage	12kg per regeneration	
Voltage	240 volts with 24 volts step down transformer	
N. I. D. I. I.	·c·	1 1 1 20 0

Note: Product specifications are a guide only and can change without notice.

## Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160 Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com www.waterwaysproducts.com