



To us it's more than just water...

3672-3150 Water Softener

Commercial Automatic

WATERWAYS

Quality ways with water

Est-1987

Product Description: Water softeners are typically used for removing calcium carbonate, manganese, iron and hardness from water sources and are regenerated by brine solutions. The treated water is soft and non scaling/staining. Commercial systems are available in single or twin (duplex) models and domestic units are available in cabinet style models.

Specifications

Type	Automatic Water Softener	
Description	Self standing pressure vessel (blue) with top mounted valve and separate brine tank (black)	
Capacity	220,000 litres at 100 mg/l hardness	
Media Tank	36" (91cm) x 72" (183cm) wound fibreglass pressure vessel	
Resin Capacity	550 litres of fine mesh cation resin	
Control Valve	Fleck 3150 5 stage regeneration Industrial Valve Volume (on demand) regeneration	
Brine Tank	30" (76cm) x 48" (122cm) with lid	
Distributor	Hubs and laterals water distribution	
Flow Rate	Continuous	300 litres per minute
	Peak	330 litres per minute
Pressure	Maximum	600 kpa (85psi)
	Minimum	175 kpa (25psi)
Pipe Sizes	Inlet/outlet	2" (50mm)
	Drain	1" (25mm)
Salt Usage	22kg per regeneration	
Voltage	240 volts with 24 volts step down transformer	

Note: Product specifications are a guide only and can change without notice.