

SEV34 Volumatic Water Softener

Domestic

WATERWAYS

Quality ways with water

.ex:2981

Product Description: Water softeners are typically used for removing calcium carbonate, manganese, iron and hardness from water sources and are regenerated by brine solutions. The treated water is soft and non scaling/staining. Commercial systems are available in single or twin (duplex) models and domestic units are available in cabinet style models.

Specifications

•		
Туре	Automatic Water Softener	
Description	Self standing pressure vessel (blue) with top mounted valve and separate brine tank (black)	
Capacity	34,000 litres at 100 mg/l hardness	
Media Tank	13" (33cm) x 54" (137cm) wound fibreglass pressure vessel	
Resin Capacity	56 litres of fine mesh cation resin	
Control Valve	Fleck 5000 electronic 5 stage regeneration fully adjustable functions Microprocessor control	
Brine Tank	18" (46cm) x 40" (102cm) with lid	
Flow Rate	Continuous Peak	40 litres per minute 50 litres per minute
Pressure	Maximum Minimum	600 kpa (85psi) 175 kpa (25psi)
Pipe Sizes	Inlet/outlet Drain	3/4" (20mm) 1/2" (15mm)
Salt Usage	8kg per regeneration	
Voltage	240 volts with 24 volts step down transformer	
N. I. D. I. I.	·c·	1 1 1 20 1

Note: Product specifications are a guide only and can change without notice.

Waterways Products (Aust) Pty Ltd

23 Aldershot Road, Lonsdale SA 5160 PO Box 443 Lonsdale DC SA 5160 Telephone 08 8186 0189 Facsimile 08 8382 7488 Email: enquiries@waterwaysproducts.com www.waterwaysproducts.com